

SAFETY DATA SHEET

Page 1 of 5

Date Prepared: May 1, 2015

1. Product and Company Identification

RJ Stacey Ltd. P.O. Box 529 Lake Orion, MI 48361 Phone (248) 330-4707

> Product Name: Product Type: Product Description: General Use :

RJS-770-L Sealant Compound Brown Liquid Injectable Sealant

2. Hazards Identification

GHS Classification :

Carcinogenicity, 1A Skin Irritation, 2 Eye Irritation, 2B Aspiration Hazard, 1

GHS Label Elements : Signal Word : Warning



Hazard Statements:

H315 / 320 Causes Skin and Eye Irritation H333 May be harmful if inhaled (respirable dust, see NOTE below) H303 May be harmful if swallowed H335 May cause respiratory irritation

Precautionary Statements :

P261 Avoid breathing dust/vapors P262 Do not get in eyes, on skin, or on clothing P285 In case of inadequate ventilation wear respiratory protection P281 Use personal protective equipment as required P301/P330/P331 If Swallowed : Rinse mouth, Do NOT induce vomiting. P301/P310 If Swallowed : Immediately call a Poison Center or Physician P333/P313 If skin irritation or rash develops: Get medical attention. P302/P352 If on skin: Wash with plenty of soap and water P305/P351/P338 If in eyes : Rinse cautiously with water for several minutes. Remove contact lenses if easy to do. Continue Rinsing.

P337/P313 If eye irritation persists: Get medical attention

P342/P311 If experiencing respiratory symptoms : Get medical attention.

P233 Keep container tightly closed

P210 Keep away from open flames. - No Smoking

P501 Dispose of observing all Federal, State and Local regulations.

NOTE: THIS PRODUCT IN ITS PURCHASED FORM DOES NOT PRESENT AN INHALATION HAZARD FROM FIBERS OR DUST, AS IT IS A LIQUID DUST IS NOT AIRBORN UNDER NORMAL HANDLING.

3. Composition / Information on Ingredients

Ingredients	CAS No.	% by weight
Solvent Mixture Crystalline Silica	64742-47-8 None	1-20 <2
Modified Natural Resins	Proprietary	75-100

4. First Aid Measures

Ingestion:	DO NOT INGEST. Oral toxicity not determined. Do NOT induce vomiting. Even small amount of solvent aspirated into the lungs during ingestion or vomiting may cause aspiration pneumonitis. If vomiting occurs spontaneously, keep head below hips to prevent aspiration
	Call a physician or get medical help immediately.
Inhalation:	Remove to fresh air. If symptoms persist,
	seek medical attention.
Skin Contact:	Wash with soap and water, consult physician if
	rash develops.
Eve Contact:	Flush with water 15 minutes. If symptoms persist,
	seek medical attention.

5. Fire Fighting Measures

Recommended Extinguishing Agent: Foam, Dry Chemical, Carbon Dioxide, Water Fog Special Fire Fighting Procedures: Self contained breathing apparatus and protective clothing should be worn in fighting fires involving chemicals. (Professionally Trained Personnel). Hazardous Products Formed by Fire or Thermal Decomposition: CO, CO2, H2S, SO2, Smoke, Incomplete Combustion Products Unusual Fire or Explosion Hazards: Closed containers may rupture when exposed to extreme heat or fire conditions Compressed Gases: None Pressure at Room Temperature: Does not apply

6. Accidental Release Measures

Steps to be taken in cases of

spill or leak:

Wear proper personal protective equipment. Remove any sources of ignition from the area and allow hot surfaces to cool. Return uncontaminated material to metal container and seal container tightly. Dispose of contaminated material or waste. Clean up with mineral spirits.

7. Handling and Storage

Storage: Cool, dry, storage below 90 degrees F. Store in closed containers. Refrigerate for best shelf life.

Handling: Avoid contact with skin and eyes. Do not breathe vapors. This product in its purchased form does not create an inhalation hazard from fibers or dust. If grinding or sanding or any other process is performed to this compound will cause airborne particles wear appropriate respirator to avoid breathing any dust or vapors. Wear appropriate safety gear as required in work area.

SDS

8.	Exposure Controls / Personal Protection				
	Exposure Limits Ingredients (TLV)	(PEL)	ACGIH	OSHA	OTHER
	Crystalline Silica Cristobalite Tridymite Quartz	0.	05 mg/m3 (respirable) 05 mg/m3 (respirable) 1 mg/m3 (respirable)	0.025 mg/m3 (respirable) 0.025 mg/m3 (respirable)	
	Solvent Mixture		100ppm TWA	500ppm TWA	
	Modified Natural R	esins	10mg/m3	15mg/m3	
	Personal Protective Equipment (PPE) Eyes: Safety Glasses Full face shield recommended. (during injection process)				
	Skin: Chemical resistant gloves. Respiratory Protection:				
	NIOSH approved for organic vapors and dust. Other Protective Clothing or Equipment: Coveralls or other protective clothing. Safety equipment as required in area. Work / Hygienic Practices: Avoid contact with skin. Wash hands before eating.				
	Engineering Controls : Ventilation: Local exhaust if poorly ventilated area or in confined spaces. Ventilation should be provided during heat up to exhaust organic vapors resulting from vaporization of certain organic agents				
0	Chamical and Physical	Proportion			

9. <u>Chemical and Physical Properties</u>

Appearance:	Brown Liquid		
Odor:	Solvent like		
pH:	6.3		
Solubility in Water:	NIL		
Specific Gravity:	1.0 (uncured) (H2O =1))	
Evaporation Rate:	Not Applicable	-	
Boiling Point:	Not Applicable		
Melting Point:	Not Applicable		
Vapor Pressure:	Solvent only, mixture not tested :		
	0.6 kPa	(2.2 mm Hg) at 20 C	
Vapor Density:	Solvent only, mixture not tested		
	5.5 (ai	ir =1)	
VOC Content:	Max 14% by weight	,	
Flash Point:	160 ⁰ F.	Method: ASTM D93	Pensky-Martens Closed Cup

Flammable Limits:

LEL: Not Established UEL: Not Established

10. Stability and Reactivity

Stability:	Stable
Hazardous Polymerization:	Will not occur
Hazardous Decomposition	
Or By-Products:	CO, CO2, H2S, SO2, Smoke, Incomplete Combustion Products
Incompatibility:	Strong Oxidizers and Strong Acids, Mineral Acids,
	Alkalies,

11.	Toxicology Information		
	Primary Routes of Entry: Signs and Symptoms of Overexposure:		Inhalation and contact. Inhalation: Possible dizziness or headaches, respiratory irritation. Eyes: Redness and irritation. Skin: Chemical dermatitis, redness and itching.
	Existing Conditions Aggra by Exposure:	avated	Pre-existing skin condition if prolonged exposure to skin. (Wear chemical resistant gloves) Respiratory disorders, asthma, chronic emphysema, heart condition (if prolonged and continuous exposure to dust or vapors). Dust exposure is not a hazard with this product under normal use. Product is in a liquid form. (Organic vapors, Wear recommended respirator if exceeding permissible exposure limit, see section 8)
	Carcinogenicity NTP:	Crystalline Si	lica (respirable size) Known to be a Carcinogen
	IARC:	Crystalline S	ilica, Group 1 IARC
	OSHA Regulated: Toxicity : (Solvent only, r Inhalation (Solvent): Skin (Solvent): Ingestion: (Solvent):	Low Exp	ed) Toxicity: LC50 greater than near-saturated vapor concentration / 1 hour rat ected to be of Low Toxicity : LD50.2000 mg/kg, Rat mg/kg, rat ected to be of Low Toxicity : LD50>2000 mg/kg, rat
	Acute Health Hazards:	redr Inhalation: I or h	tact on bare skin can cause chemical dermatitis, ness, itching Breathing excessive vapors may cause dizziness eadaches irritation of eyes, nose, throat, lungs and
	Chronic Health Hazards:	Inhalation: Rep nerv	cause central nervous system depression. Crystalline Silica, respirable size NTP Known Carcinogen. eated exposure to solvent vapors above recommended exposure limits, can cause central /ous system effects, drowsiness, dizziness and headaches. ear recommended respirator if exceeding permissible exposure limit, see section 8)
			HASED FORM DOES NOT PRESENT AN 5 OR DUST, AS IT IS A LIQUID.

12. Ecological Information

Solvent Only : Expected to have low toxicity. LC/EC/IC50 > 1000 mg/l, Fish, Aquatic Invertebrates, Algae, Microorganisms. Mobility - Absorbs to soil and has low mobility. Floats on water.

13. Disposal Considerations

Recommended Methods of Disposal: RCRA 40 CFR 261 Classification : This product as purchased does not fall under current US EPA RCRA definitions of Hazardous Waste. Contains solvent, do not let waste contaminate soil or water. Certain state regulations could affect whether a material is considered a hazardous waste upon disposal. It must also be noted that a material can become a hazardous waste if it is mixed with or comes in contact with a hazardous substance during use. Under RCRA it is the responsibility of user of a product to determine at the time of disposal, whether a material should be classified as a hazardous

14. Transport Information

waste.

DOT (49 CFR 172):	Not Regulated*
	*Not Regulated under 49 CFR if in a container of 119 gallon capacity or less.

IATA : Not Regulated

Liquid / Solid (per ASTM D 4359-90) : Material is a liquid

DUST IS NOT AIRBORN UNDER NORMAL HANDLING.

15. REGULATORY INFORMATION

CERCLA HAZARDOUS SUBSTANCES (40 CFR Part 302.4): This product is not reportable under 40 CFR Part 302.4.

SARA TITLE III SECTION 302 EXTREMELY HAZARDOUS SUBSTANCES (40 CFR Part 355): This product does not contain any SARA 302 Extremely Hazardous Substances.

SARA TITLE III SECTION 311/312 HAZARDOUS CATEGORIZATION (40 CFR Part 370): Certain ingredients of this product are regulated under Sara Title III Section 311/312, see section 3 of this MSDS.

SARA TITLE III SECTION 313 (40 CFR Part 372): None

U.S. INVENTORY (TSCA): Any chemical substances (as defined in 40 CFR Part 710.2), that are contained in, or used in the manufacture of this product, are reported in the EPA TSCA Inventory. (As required per 40 CFR 710.3)

CALIFORNIA PROPOSITION 65: Crystalline Silica

CANADA WHMIS: Ingredient Disclosure List: Crystalline Silica, quartz -- Crystalline Silica, Tridymite --Crystalline Silica, Cristobalite, Solvent Mixture 64742-47-8 WHMIS Classification : Solvent Mixture, B3, Crystalline Silica, quartz:, D2A

EUROPEAN UNION : Crystalline Silica: CLP Carc.1A, Solvent 64742-47-8:CLP Asp Tox 1

OZONE DEPLETERS: * This product is not manufactured with or contains any Class I or Class II Ozone Depleting Chemicals. (ODC's)

NOTE: THIS PRODUCT IN ITS PURCHASED FORM DOES NOT PRESENT AN INHALATION HAZARD FROM FIBERS OR DUST AS IT IS A LIQUID. DUST IS NOT AIRBORN UNDER NORMAL HANDLING.

16. OTHER INFORMATION

The information contained in this MSDS sheet is based upon data supplied by our suppliers and data determined by us in our facilities at the time these products were formulated. We have reviewed any information that we received from sources outside our company. We believe that information to be correct but cannot guarantee its accuracy or completeness. Health and safety data in this sheet may not be adequate for all individuals and/or situations. It is the user's obligation to evaluate and use this product safely and to comply with all applicable laws and regulations. If after reviewing this MSDS you have determined that this product poses unusual risks to you, your plant, or your plant personnel, or if you cannot comply fully with all safety recommendations, do not use this product. This product is intended for a temporary repair. The responsibility for whether or not the product is suitable for use rest solely with the purchaser. We recommend that the product be tested prior to use. Your use of this information is beyond our control, therefore, the information is provided without warranty expressed or implied. We accept no liability beyond the purchase price of the material.

Estimated HMIS® Code:

Health Hazard:	* 1	* See section 11 for chronic effects.
Flammability Hazard:	2	
Physical Hazard:	0	
Personal Protection:	NPCA recommends that PPE	E codes be determined by the employer, who is familiar with the actual
	conditions under which chem	icals in the facility are used.

Procedural Warning:

Attn: Technician

(For industrial use by professionally trained personnel only) When the compound is curing, vapors and gasses are given off and should be vented. Steps should be taken to insure that the injection pressure in conjunction with pressure that may occur from gassing off does not exceed the pressure limitations of the piping system. Also, be aware it is quite common that the application temperature will exceed the compound flash point. Be aware of the possibility of a flash and take necessary precautions. Avoid contact with skin and eyes. See section 8 of SDS for personal protective equipment. Ventilation may be needed during heating/curing stage to exhaust organic vapors resulting from vaporization of certain organic agents. Always avoid direct contact with smoke and vapors being emitted from the compound during the heating/curing process. These vapors may be irritating to the skin, eyes and respiratory system. Read product technical data and safety information before use.

PREPARATION INFORMATION

Prepared By:	Safety Department
Company:	RJ Stacey Ltd.
Revision Date:	05-01-15 Revision: B